



Daylight whites

FRENCH OAK ZENITUDE TUFEAU, HERRINGBONE 139 TONGUE & GROOVE / 14 MM

Characteristics

Species: French oak Origin: France

Grading: Zenitude - light and dark wood, black knots, filled knots, opened knots, discolouration, cracks, splits, sapwood. Grade with all pecularities of the wood without limitation. The size of the knots is proportional to the width of the planks.

Finish: Tufeau - unbrushed, chalk-tone matt oiled / Hard wax oil

For oiled wood floors, apply a thin coat of Panaget maintenance oil right after installation. Please refer to our maintenance guide. While we take the greatest care in manufacturing our flooring, there can sometimes be slight variations in colouring. So it's important to factor in margin of 2-5% more than the actual surface you're covering. This means you won't run out of planks and you will be sure to enjoy a beautiful finished product.

Design

Engineered single plank, herringbone made under the patent EN 13489 Tongue & Groove



Description

Width: 139 mm Length: 800 mm Thickness: 14 mm Top layer: 3.4 mm Core: plywood

Counterbalance: unrolled wood **Profile:** 4 bevels with 2 aged

Packing

Sqm/pack: 2.22 Pack/pallet: 32 Sqm/pallet: 71.04 Weight/sqm: 7.4 kg Weight/pallet: 525.7 kg

Installation method



Floating glued installation under the patent DTU 51.11



Glue down installation under the patent DTU 51.2



Floating installation using plastic DPM and Isol 20 or fully glue down using Presto PM







* Emissions of volatile substances which could toxic if inhaled. These are rated on a scale from (very low) to C (high).







PANAGET - 3 rue d'Orgères - 35230 Bourgbarré - FRANCE tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com



DECLARATION OF PERFORMANCE

NO 1007658



Unique identification code of the product-type: Herringbone 139 Tongue & Groove, 14 mm, French oak

Intented use/es: Engineered single plank, herringbone made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: No4

Harmonised standard: EN 14342: 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction to fire	Dfl-s1	
Features for this classification:		
- Average minimum density (Kg/m³)	500	EN 14342 : 2013
- Average thickness (mm)	14	
- Intented use, fitting mode	Floating fit	
Formaldéhyde emission	E1	EN 717-1
Content of pentachlorophénol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A+ < 1µg/m³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7
Thermal resistance (m ² .K/W)	0.108	
Biological sustainability	Classe 1	EN 335

N/A: Not Applicate

The performance of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011. under the sole responsability of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 12 november 2019

Carole FRANÇOIS

^{*}VOC: Volatile Organic Compounds

^{**}CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1 and 2 category