



Naturels Intemporels



No 1017917

## FRENCH OAK ZENITUDE SABLE, DIVA 184 CLICK / 12 MM

### Characteristics

**Species:** French oak **Origin:** France

**Grading: Zenitude** - light and dark wood, black knots, filled knots, opened knots, discolouration, cracks, splits, sapwood. Grade with all peculiarities of the wood without limitation. The size of the knots is proportional to the width of the planks.

**Finish: Sable** - natural brushed, white patina matt oiled / Hard wax oil

For oiled wood floors, apply a thin coat of Panaget maintenance oil right after installation. Please refer to our maintenance guide. While we take the greatest care in manufacturing our flooring, there can sometimes be slight variations in colouring. So it's important to factor in margin of 2-5% more than the actual surface you're covering. This means you won't run out of planks and you will be sure to enjoy a beautiful finished product.

### Design

Engineered extra-wide single plank made under the patent EN 13489  
Click system made under Unilin patent NoEP1640530

### Description

**Width:** 184 mm  
**Length:** 495 to 1992 mm  
**Thickness:** 12 mm  
**Top layer:** 2.5 mm  
**Core:** HDF\*  
**Counterbalance:** unrolled wood  
**Profile:** 4 bevels

\*High Density Fiber Board

### Packing

**Sqm/pack:** 2.20  
**Pack/pallet:** 40  
**Sqm/pallet:** 88.00  
**Weight/sqm:** 9.9 kg  
**Weight/pallet:** 871.2 kg



### Installation method



Glue-free floating installation under the patent DTU 51.11



Glue down installation under the patent DTU 51.2



Floating installation using plastic DPM and Isol 20 or fully glue down using Presto PM



Fully glue down using Presto PM



\* Emissions of volatile substances which could be toxic if inhaled. These are rated on a scale from A+ (very low) to C (high).





# DECLARATION OF PERFORMANCE

## NO 1017917

**Unique identification code of the product-type:** Diva 184 Click, 12 mm, French oak

**Intended use/es:** Engineered extra-wide single plank made under the patent EN 13489  
Glue-free floating installation under the patent DTU 51.11

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** No4

**Harmonised standard:** EN 14342 : 2013

### Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction to fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m <sup>3</sup> ) - Average thickness (mm) - Intended use, fitting mode	500 12 Floating fit		
Formaldéhyde emission	E1		EN 717-1
Content of pentachlorophénol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVP0910046A)	Classe A+ < 1µg/m <sup>3</sup>	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7	
Thermal resistance (m <sup>2</sup> .K/W)	0.080		
Biological sustainability	Classe 1	EN 335	

N/A: Not Applicable

\*VOC: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1 and 2 category

The performance of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011. under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 15 november 2019

**Carole FRANÇOIS**

