



GLUE PRESTO PM

NOTE

- ✓ Glue for full-surface gluing of solid and engineered parquet, imperative for underfloor heating/cooling (only use the brand names prescribed by the manufacturer).
- ✓ Single component silane modified glue. MS Polymer cross-links on contact with air or substrate humidity.
- ✓ This adhesive contains no isocyanate or silicone.
- ✓ Aspect: Thixotropic paste.
- ✓ Colour: Sunny beige
- ✓ Density at 20°C: about 1.65
- ✓ Viscosity (Brookfield): 80.000 mPa.s
- ✓ Application temperature: >10°C <35°C
- ✓ Curing rate at 23°C and 50% RH: >3 mm/24h
- ✓ Flammable classification
- ✓ Protect to freeze.
- ✓ Supports: Concrete or anhydrite screed, CTBH, CTBX wood, tiles, heating/cooling supports.
- ✓ The use of a primer promoter is not required.
- ✓ Application: B3 trowel. 4x4 notched, stainless steel.

Packaging: Box containing 1 x 7.5 kg sachet or 1 bucket (2x7.6kg).

Consumption: 1.2 kg / sqm

Storage: shelf life is 12 months in original closed packaging, if stored between 5°C and 25°C

Follow the data of the wood flooring manufacturer and the applicable DTU.

