



OAK ASTER OILED

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	131246200	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969302500	Design	1-strip	content		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic	Minimun Mean Density kg/m³ >500 kg/m³		
		Range	Kährs Wood Classic	Reaction To Fire	EN13501-1	Dfl-s1
		Collection	Flora Collection	Formaldehyde Emission	EN717-1	E1
Refining Treatment	Microbevelled 4-sided, Brushed	Natural/Stained	Natural			
		Brinell Value	3,7	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Dimensions	187 x 2000 mm	loint	Woodloc® 5G	Breaking Strength N/mm²	EN1533	NPD
Weight per Package	21.5 kg	Floor heating	Yes			
Area per Package	2.99 m ²	Wear-layer material	Hardwood	Thermal	EN12664	0.14 \\//ma//
Area per pallet	134.55 m ²			Conductivity		0,14 W/mK
Package info	Packages may contain start and stop boards.	Wear Layer Thickness	2.6 mm		anso D Value	.09 (m2K/W)
		Core material	Pine/Spruce lamella	Thermal Resistance R-Value		.09 (1112K/VV)
		Backside material	Spruce	Biological Durability	EN350-2	Class 1
			13 mm	CARB2		Compliant
		Installation method	Floating, Glue-down	Slipperiness	CEN/TS15676	'
		LRV	40	Suppermess	CLIV/13130/0	INI

Other products in this collection









OAK GENTIAN **OAK EDELWEISS** OAK ASTER

CERTIFICATES





Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.