



OAK ANEMONE 200

Oak Anemone features a soft white-wash with subtle grey undertones, delicately balancing the darker wood with the overall even tone of the oak. This creates a sleek, modern design that preserves the warmth and natural beauty of the wood. The smooth, matt lacquered finish enhances the clean, and calm wood design.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	131257200 / 7393969305327	range		
Design / Wood Species	1-strip / Oak	LRV / LRV Std1 / LRV Std2	41 / 3.3 / 6.6	
Surface Treatment /	Matt lacquer / Stained	Warranty	20 years	
Natural/Stained		TECHNICAL PROPERTIES	=	
Refining Treatment	Microbevelled 4-sided, Brushed	Moisture content	FN13183	7%±2%
Width x Length x Thickness	187 x 2000 x 13 mm	Minimun Mean Density	LIVIDIOD	>500 kg/m ³
Weight per package / per	21 kg / 7.2 kg	kg/m ³		>500 kg/III
m2		Reaction To Fire	EN13501-1	Dfl-s1
Area per package / per	2.99 m ² / 134.55 m ²	Formaldehyde Emission	EN717-1	E1
pallet		Content PCP	CEN/TR14823	≤ 5 x 10-6n
Grading	Calm	Breaking Strength N/mm ²	EN1533	NPD
Joint	Woodloc® 5G		EN350-2	Class 1
Installation method	Floating, Glue-down	——— Biological Durability ——— CARB2	EINSSU-Z	
Floor heating	Yes		CEN/TS15676	Compliant
Wear leayer material /	Hardwood / 2.6 mm	Slip resistance	CEN/1313070	NPD
thickness		CONSCINI GANS LAS PRIFESUS		
Resandable	2 times	A+		
Core material	Pine/Spruce lamella			
Backside material	Spruce			

DETAILED DESCRIPTION

Colour change : Stained product - noticable colour change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK YARROW



OAK ASTER MATT



OAK EDELWEISS



OAK GENTIAN



OAK ASTER OILED



OAK PRIMROSE



OAK LUPINE



OAK LAVENDER



OAK ZINNIA