



OAK SAND

Oak Sand is a beautiful and warm yet light and lively oak floor, bringing your thoughts to summer beaches. It is a 3-strip, matt lacquered floor with lots of character. Oak Sand is ideal for any interior where you are looking for a natural and light floor for a homely feeling.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	133B22EK1KKW226	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969048408	Board	3-strip	Minimum Mean Density kg/m³ >500 kg/m³		
Surface treatment	Matt lacquer	Grading	Lively	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	2266 x 188 x 13 mm	Range	Kährs Avanti	Formaldehyde Emission	EN717-1	E1
Weight per Package (kg)	24.55 kg	Collection	Ground Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package (m²)	3.41 m²	Resandable	2-3 times	Breaking Strength N/mm²	EN1533	NPD
Area per pallet (m²)	119.35 m²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Brinell Value	3,7	Thermal Resistance R-Value	.09 (m2K/W)	
DETAIL DESCRIPTION		Joint	Woodloc® 5G	Biological Durability	EN350-2	Class 1
		Floor heating	Yes	CARB2		
		Warranty	20 years	Compliant		
		Wear-layer material	Hardwood			
		Wear-layer thickness	2.6 mm			
COLOUR CHANGE		Core material	Pine/Spruce lamella			
		LRV	40			
		Installation method	Floating, Glue-down			
Stained product - noticeable color change over time.						



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.