



## OAK PALAZZO ROVERE

Oak Palazzo Rovere is a floor with the strips laid in a Dutch pattern. The floor is supplied in finished boards and installed in the same simple way as Kährs' other multi layer parquet flooring. A certain amount of attention must be paid to the pattern when laying the floor.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	153138EK50KW 0	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969024150	Design	Pattern	content		
Surface Treatment	Satin lacquer	Grading	Variation	Minimun Mean Density kg/m³ >500 kg/m³		
Dimensions	2426 x 198.5 x 15 mm	Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	23 kg 2.9	Collection	European Renaissance Collection	Formaldehyde	•	E1
Area per Package				Emission		
Area per pallet (m²)	130	Natural/Stained	Natural	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Package info	Packages may contain start and stop boards.	Brinell Value	3,7	Breaking EN1533 Strength N/mm²	EN1533	NPD
		Joint	Woodloc® 5S			
		Floor heating	Yes			
DETAIL DESCRIPTION		Wear-layer material	Hardwood	<ul><li>Thermal Conductivity</li></ul>	EN12664	0,14 W/mK
Even colour with minor variations. Sapwood may occur. Small sized knots in limited numbers allowed.		Core material	Pine/Spruce lamella	Thermal Resistance R-Value		.11 (m2K/W)
		Thickness	15 mm	Biological	EN350-2	Class 1
COLOUR CHANGE		Installation method	Glue-down, Floating	Durability		
Some muting of colour variation to medium, straw brown.				CARB2		Compliant



## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.