



- The new Kährs Flex Silent is a permanent elastic underlay, specially designed for floating installation under parquet and laminate floors, meant to offer a high class impact sound and walking noise reduction.
- Exceptionally long-lasting, survives two or more top coverings with nearly always 100% performance
- Made from 90% natural raw materials, supports a healthy living environment
- High energy efficiency - reduces heating costs thanks to the low thermal resistance
- Specifically designed for the floating installation with 20 cm overlap included
- Excellent long-term walking sound reduction – up to 30%
- Extreme high as well as sustainable compressive strengths
- Improvement of the walking comfort (absorbing characteristics, walking-over and splicing)
- FREE of plasticizers, formaldehyde and heavy metals, solvent free and does not contain any other ozone-depleting substances.

ARTICLE NUMBER:

710185

	Impact Sound	<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>
	Compressive strength	<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>
	Leveling Effect	<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>
	Walking Comfort	<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>
	Underfloor Heating	<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>
	Moisture Management	<input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/> <input type="radio"/>



TECHNICAL DATA

Product	Kährs Flex Silent
Product code	710185
Material	PU + mineral fillers + castor and rapeseeds oil
Type of format	roll
Thickness	2,5 mm
Density	800 for 2.5 kg/m
Impact Sound IS	18 - 20 Db
Compressive strength CS	> 170 kPa
Compressive creep CC	> 35 kPa
Dynamic load DL	> 2 500 000
Punctual conformability PC	1,3 mm
Thermal resistance TR	0,01 m ² K/W
Water vapor resistance SD	≥100 m
Certifications	Blue Angel

