

NOBLE

WOOD - PRODUCT DATASHEET 2021



TECHNICAL DATA (EN 13489)

| | | |
|---|---|-------------------------|
| Reaction to fire | EN 14342 Table 1 | Dfl-s1* |
| Emission of formaldehyde | EN 14342 | E1 |
| Brinell hardness (average value) Oak | (BHN) EN1534 | 3,7 |
| Taber Abraser/Lacquer's wear resistance Proteco Lacquer Proteco Hardwax Oil <i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i> | EN 13696 | 4000 N/A |
| Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II | EN ISO 10140-3 / EN ISO 717-2 | ≥ 17 |
| Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II | EN ISO 10456:2007 | 0,132 0,152 0,172 |
| Thermal conductivity (W/m K) | EN 12664 / EN 14342:2013 | 0,121 |
| Construction | 4-layer with softwood veneer and lamella core | |
| * Cfl-s1 for lacquered products can be provided on demand. | | |

INSTALLATION

| | | |
|---|--|--|
| Installation method | 2-lock for floating or glue down | |
| Installation instruction | Download from www.tarkett.com Contact your supplier for more details | |
| Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system | Yes | |
| Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m² | | |

RECOMMENDED ACCESSORIES

| | |
|--|--|
| Installation | Tarkofoam II / Tarkoflex II Installation kit |
| Aesthetics | Skirting Transition moulding Pipe covers |
| Care & Maintenance | Wood Floor Care Kit / Spray Mop Kit Bioclean Hardwax Oil Refresher Hardwax Oil |
| See more alternatives and the complete range of accessories @ www.tarkett.com | |

MAINTENANCE

These Tarkett wooden floors have a Proteco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details, such as saw marks. Please always refer to maintenance guidance available on websites.

See maintenance instructions @ www.tarkett.com

Noble Proteco Lacquer

| | |
|----------------------|------------|
| 97 % 97 % | 100 % |
| Natural Renewable | Recyclable |

Noble Proteco Hardwax Oil

| | |
|----------------------|------------|
| 98 % 98 % | 100 % |
| Natural Renewable | Recyclable |



2-LOCK



www.realwood.eu

NOBLE

WOOD - PRODUCT DATASHEET 2021

DESIGN

A timeless floor inspired by the classic modular technique from the 1950s. This revisited design offers a contemporary look thanks to a special surface brushing that allows the light to reflect on the surface in new and exciting ways. Each squared lamella is applied by hand, to create a block pattern, on top of Tarkett's engineered and layered construction. The random combination of nuances in the colour of natural oak allows every installer to compose stunning visual patterns, that will change depending on the installation and the incoming light. Thanks to this wonderful handcrafted work with alternating grain directions, colour variations and twisted designs, every floor becomes a unique and exclusive creation. We like to call it "perfect imperfection".

| PRODUCT DATA | Material code | Dimensions LxWxH (mm) | Pattern | Surface treatment | Surface effect | Bevel | Character | Colour | Latin name | DoP no. | Wear layer thk (mm) | Board/ pack | m2/ pack | m2/ pallet | Net weight/ m2 (kg) |
|-----------------------|---------------|-----------------------|--------------|---------------------|----------------|-------|-----------|------------|------------|-----------|---------------------|-------------|----------|------------|---------------------|
| Noble Oak Scandinavia | 7806008 | 2 028 x 192 x 16 | Basket Weave | Proteco Hardwax Oil | Brushed | - | Lively | White | 1 | 0190-0123 | 3,5 | 6 | 2,34 | 81,9 | 9,0 |
| Noble Oak Manhattan | 7806014 | 2 280 x 190 x 16 | Small Block | Proteco Hardwax Oil | Brushed | - | Lively | White | 1 | 0190-0123 | 3,5 | 6 | 2,60 | 91,0 | 9,0 |
| Noble Oak Brooklyn | 7806903 | 2 280 x 190 x 16 | Big Block | Proteco Hardwax Oil | Brushed | - | Calm | White | 1 | 0190-0123 | 3,5 | 6 | 2,60 | 91,0 | 9,0 |
| Noble Oak Art Deco | 7806009 | 2 028 x 192 x 16 | Basket Weave | Proteco Hardwax Oil | Brushed | - | Lively | Warm beige | 1 | 0190-0123 | 3,5 | 6 | 2,34 | 81,9 | 9,0 |
| Noble Oak Soho | 7806012 | 2 280 x 190 x 16 | Big Block | Proteco Hardwax Oil | Brushed | - | Calm | Warm beige | 1 | 0190-0123 | 3,5 | 6 | 2,60 | 91,0 | 9,0 |
| Noble Oak Retro | 7806007 | 2 028 x 192 x 16 | Basket Weave | Proteco Lacquer | - | - | Lively | Warm brown | 1 | 0190-0123 | 3,5 | 6 | 2,34 | 81,9 | 9,0 |
| Noble Oak Wasa | 7806010 | 2 028 x 192 x 16 | Basket Weave | Proteco Hardwax Oil | Brushed | - | Lively | Warm brown | 1 | 0190-0123 | 3,5 | 6 | 2,34 | 81,9 | 9,0 |
| Noble Oak Chelsea | 7806016 | 2 280 x 190 x 16 | Small Block | Proteco Hardwax Oil | Brushed | - | Lively | Warm brown | 1 | 0190-0123 | 3,5 | 6 | 2,60 | 91,0 | 9,0 |
| Noble Oak Bronx | 7806017 | 2 280 x 190 x 16 | Big Block | Proteco Hardwax Oil | Brushed | - | Lively | Warm grey | 1 | 0190-0123 | 3,5 | 6 | 2,60 | 91,0 | 9,0 |
| Noble Oak Broadway | 7806013 | 2 280 x 190 x 16 | Big Block | Proteco Hardwax Oil | Brushed | - | Calm | Black | 1 | 0190-0123 | 3,5 | 6 | 2,60 | 91,0 | 9,0 |

Due to the nature of the material this table shows typical values.

1: Quercus Robur & Quercus Petraea



Noble Oak Scandinavia



Noble Oak Manhattan



Noble Oak Brooklyn



Noble Oak Art Deco



Noble Oak Soho



Noble Oak Retro




Noble Oak Wasa



Noble Oak Chelsea



Noble Oak Bronx



Noble Oak Broadway

The pictures only present the colour of the floor. For more details regarding grading and variations see the Grading Book or www.tarkett.com.

Tarkett's international range of floors comprises many different products. Some of these may not be for sale in your country. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.

For further and latest information please visit www.tarkett.com