

Specification

Species:	European Oak		
Finish:	Brushed & Oiled		
Size:	14 x 190 x 1820mm		

## Colour and grain

## Colour:

• Heartwood is light brown; some boards may have a pinkish tint or a slight greyish cast. Sapwood is white to cream. Dark stain applied to enhance the aged look of the flooring.

## Grain:

• Open, with longer rays than red oak. Occasional crotches, swirls and burls. Plain sawn boards have a plumed or flared grain appearance. Softer grain is removed in the brushing

## Variations Within Species And Grades:

• Considerable variation among boards in colour, grain texture and sapwood.

Specification				
Board Dimensions:	14 x 190 x 1820mm (3mm wear layer)			
Grade:	Rustic 'B/C/D (Repaired Knots upto 80mm in grade D + Small Repaired Splits allowed)			
Oak origin:	Mixed EU Sources			
Profile:	Uniclic			
Bevel:	B4 1.2mm 'long & short edge'			
Pack Size:	2.0748 M2			
Planks per pack:	6 Layers 1820mm, up to 30% starter boards (600mm +)			
Construction:	Oak Wear Layer, Spruce Core, Pine Back			
Oil / Lacquer :	UV Cured Oil			
Sapwood Allowed:	Yes upto 15%			
Adhesive:	E1			
Bathroom:	Must never Install in this area			
Conservatory:	Yes			
Float Install:	Yes - Over Underlay			
Guarantee:	25 Years Structural - 1 Year Finish			
Under floor heating:	Yes if installed as a floating floor over underlay incorporating DPM and a			
Embedded systems	maximum contact temperature of 27°C (back of the board and sub floor)			
Maintenance:	Elka Oil maintenance kit			
Installation:	Float over underlay, full stick with Elka flex adhesive			

RUSTIC	A - Grade	B - Grade	C - Grade	D - Grade	For full grading breakdown - visit
		30%	30%	40%	www.elkaflooring.co.uk

INSTALLATION IMPLIES ACCEPTANCE NO WARRANTY WILL BE OFFERED FOR APPEARANCE RELATED CLAIMS ONCE THE PRODUCT IS INSTALLED. Please Note: Real wood flooring is a natural product, what is subject to natural variations.

Any dissatisfaction on grade quality or definition must in all cases be notified to Unilin prior to installation.

Imported and distributed by Unilin Distribution T: 0844 811 8288 visit our website for full grade specification

